



INDUSTRIAL MOTORISED SIRENS LONG RANGE SIREN 15D

SPECIFICATIONS

- Sound output 145dB(A) 1m
- Sound frequency – 480/560Hz
- *Range: Approx. 15000m in still air
- Precision CNC machined
- Aluminium fabrication
- Robust metal base
- Double Impellers
- IP Rating - IP55
- Dimensions: 500 x 600 x 560mm
- Weight: 72kg
- Packaging size: 60 x 65 x 70cm
- Shipping weight: 80kg
- Duty Cycle: Continuous
- Horizontal and level operation
- Mounting base centres: 250 x 200mm

*Range: Based on siren mounted horizontally in an elevated position in still air.

Notes: In dusty and harsh environments, a protective shield over the siren is recommended.

MODEL DETAILS

Part Number	Voltage Hz	Running Current	Starting Current
S15D415	380/415v 50Hz 3Φ	10A	102A
S15D480	460/480v 60Hz 3Φ	9A	98A

Other models, voltages and IP ratings available on request

OVERVIEW

All weather enclosed motor is ideally suited for outdoor use.

This siren would be used for audible warnings in refineries, oil rigs, in the event of fires and open-cast mining operations.

This precision manufactured unit produces a powerful low frequency sound that is ideal for long distance signalling.

