



INDUSTRIAL MOTORISED SIRENS

LONG RANGE SIREN

10S

SPECIFICATIONS

- Sound output 138dB(A) 1m
- Sound frequency – 560Hz
- *Range: Approx. 10'000m in still air
- Precision CNC machined.
- Aluminium fabrication
- Robust metal base
- Single Impeller
- Low penetrating tone
- Dimensions: 510 x 580 x 600mm
- Weight: 36kg
- Packaging size: 63 x 65 x 65cm
- Shipping weight: 43kg
- Duty Cycle: Continuous
- Horizontal and level operation
- Mounting base centres: 180 x 150mm

***Range:** Based on siren mounted horizontally in an elevated position in still air.

Notes: In dusty and harsh environments, a protective shield over the siren is recommended.

MODEL DETAILS

| Part Number | Voltage Hz | Running Current | Starting Current |
|-------------|------------------|-----------------|------------------|
| S10S415 | 380/415v 50Hz 3Φ | 7.5A | 81A |
| S10S240 | 220/240v 50Hz 1Φ | 12.5A | 102A |

Other models and voltages available on request

OVERVIEW

All weather enclosed motor is ideally suited for outdoor use.

This siren would be used for audible warnings in refineries, oil rigs, in the event of fires and open-cast mining operations.

This precision manufactured unit produces a powerful low frequency sound that is ideal for long distance signalling.

