



INDUSTRIAL MOTORISED SIRENS LONG RANGE SIREN

5S

SPECIFICATIONS

- Sound output 125dB(A) 1m
- Sound frequency – 560Hz
- *Range: Approx. 5000m in still air
- Precision CNC machined.
- Aluminium fabrication
- Robust metal base
- Single Impeller
- Low penetrating tone
- Dimensions: 410 x 410 x 500mm
- Weight: 25kg
- Packaging size: 45 x 45 x 55cm
- Shipping weight: 35kg
- Duty Cycle: Continuous
- Horizontal and level operation
- Mounting base centres: 150 x 100mm

Notes: In dusty and harsh environments, a protective shield over the siren is recommended.

***Range:** Based on siren mounted horizontally in an elevated position in still air.

MODEL DETAILS

Part Number	Voltage Hz	Running Current	Starting Current
S5S415	380/415v 50Hz 3Φ	7A	74A
S5S240	220/240v 60Hz 1Φ	12.5A	105A

Other models and voltages available on request

OVERVIEW

All weather enclosed motor is ideally suited for outdoor use.

This siren would be used for audible warnings in refineries, oil rigs, in the event of fires and open-cast mining operations.

This precision manufactured unit produces a powerful low frequency sound that is ideal for long distance signalling.

